

Drain: SKILL AND WEBB **Drain #:** 57
Improvement/Arm: JAMES C WEBB #2
Operator: J. LIVING STON **Date:** 1-14-04
Drain Classification: Urban/Rural **Year Installed:** 1898

GIS Drain Input Checklist

- Pull Source Documents for Scanning JWJ
- Digitize & Attribute Tile Drains JWJ
- Digitize & Attribute Storm Drains _____
- Digitize & Attribute SSD _____
- Digitize & Attribute Open Ditch _____
- Stamp Plans _____
- Sum drain lengths & Validate JWJ
- Enter Improvements into Posse _____
- Enter Drain Age into Posse JWJ
- Sum drain length for Watershed in Posse JWJ
- Check Database entries for errors JWJ

**Gasb 34 Footages for Historical Cost
Drain Length Log**

Drain-Improvement: Chili And WEBB - JAMES C. WEBB #2

Drain Type:	Size:	Length ()	Length (DB Query)	Length Reconcile	If Applicable	
					Price:	Cost:
TILE	16"	3245'	3245'			17847. ⁵⁰

Sum: 3245' 3245' \$17,847.⁵⁰

Final Report: 3245'

Comments:

No. 11-178

IN THE MATTER OF

James C. Webb

*Sep 7 1898
Report of James
and James's order*

*Sep 20 1898
and James's order
Report*

REPORT OF DITCH VIEWERS

COMMISSIONERS' COURT.

Filed *July 30*, 1898

Calvin Studevant

Auditor.

WM. B. BURFORD, PRINTER, INDIANAPOLIS.

Cell 11-178

To the Honorable Board of Commissioners of Hamilton County, Indiana:

We, the undersigned, appointed by this Court, at its June Term, 1898, to view a drain described in the certified copy of a petition and order of Court for a ditch, by J. B. Webb and others, handed us by the Auditor, would represent that according to said order we, on the day named therein, to-wit: the 19th day of July, 1898, in company with J. A. Mitchell, a civil engineer, made an accurate survey of the line of said proposed ditch from its source to its outlet. A plat of said ditch is filed herewith including the survey by the engineer, marked "Exhibit". We caused stakes to be set along said line, each one hundred feet, numbering down stream, as shown by plat. We also made a computation of the total number of cubic yards of earth to be removed from said drain, and estimated the total cost for the construction of the work at Six Hundred & Two $\frac{45}{100}$ Dollars. We also apportioned and set apart to each parcel of land a share of said work in proportion to the benefits received, all of which will fully appear by a tabular statement in this report. We have also set out by a statement below, the names of the owners of lands benefited with a description of each tract of land, and the amount assessed against each tract. The depth of cut, the width at bottom, and width at top along said drain is also shown in a tabular statement in this report. After a full and careful view and examination, we are of the opinion that the drain as located by the survey will be of Public utility, a benefit to the general health of the neighborhood, and will benefit two public highways, and that the cost of construction will not exceed the benefits derived therefrom, and should be a tile ditch from Stake 0. to its terminus.

The following statement shows who are benefited, the lands thereof and assessment thereon, location, length of each share, amount of assessments, amount of benefits, amount of dirt to be removed from each share, price thereof per cubic yard, and total cost of each share:

NAMES OF OWNERS.	DESCRIPTION OF LANDS.	Section.	Township.	Range.	Acres Assessed.	Ft. Assessed.	Acres Benefited.	Ft. Benefited.	Amount of Benefits.	Amount of Assessments.	From Station.		Feet Long.	Cubic Yards to be Removed.	Price per Cubic Yard.	Cost of Construction of Share.
											F	T				
Ella and O. O. Fitzpatrick	Pt. NW	NE	28	20	5	31	31		25.00	25.00	0	149	149	13		23.50
W. R. Valentine	NE SE	NW	28	20	5	3	3		5.00	5.00	149	149	30	3		4.70
Frederick Sinter	SE SE	NW	28	20	5	5	5		5.00							9.45
Same.	NE NE	SW	28	20	5	5	5		5.00	10.00	149	238	59	6		
Gas. H. Hill	SW.	NE	28	20	5	23	23		29.00							
Same.	Pt. S. S. SE.	NE	28	20	5	6	6		6.00	35.00	238	442	204	25		32.95
Rosetta Hansley	Pt. W.	SE	28	20	5	51			82.00	82.00	442	843	451	81		77.20
Jacob Mosbaugh	SW	NW	34	20	5	1	1		3.00	3.00	843	949	16	3		2.80
White River Township	Highway	N + S.	Dot	27	20	5			10.00							
Same	"	E + W	"	27	20	5			10.00	20.00	949	1045	106	25		18.85
Gas. B. Webb.	Pt. E	SE	28	20	5	58	58		96.00							
"	W.	SW	27	20	5	65	65		180.00							
"	SE	SW	27	20	5	15	15		36.00							
E. B. E. NE.		NE	23	20	5	5	5		12.00							
NW		NW	34	20	5	40	40		128.00	460.00	1045	3245	2230	675		433.00
														831		\$ 602.45

Viewer's Report of *Gas. B. W. Job. (No. 2)*

Ditch.

TABULAR STATEMENT OF STATIONS, WIDTH, DEPTH, LENGTH, ETC

STATIONS.	WIDTH AT TOP.		DEPTH OF CUT.		WIDTH AT BOTTOM.		WIDTH OF CLEARING OR TIMBER
	FEET.	INCHES.	FEET.	TENTHS.	FEET.	INCHES.	
<p>By the construction of a ditch commencing at stake 58+85 feet at the end of the tile on what is known as the James No. 10 tile ditch, and</p> <p>Running thence S 64° E from Station 0 to 0+25 = 25 feet, thence S 53° E from Station 0+25 to Station 4+25 = 100 feet. Thence South from Station 4+25 to Station 6+25 = 200 thence S 16° 30' E from Station 6+25 to 9+25 = 300 feet, thence South from Station 9+25 to 10+25 = 100 feet, thence S 25° 30' W from Station 10+25 to 12+25 = 200 feet, thence South from Station 12+25 to 13 = 75 feet, thence S 28° W from 13 to 16+50 = 350 feet, thence S 2° E from Station 16+50 to 21 = 450 feet, thence S 38° E from Station 21 to 27 = 600 feet, thence S 68° E from Station 27 to 29 = 200 feet, thence S 38° E from Station 29 to 32+45 = 345 feet, terminating at a point 180 feet west of South East Corner of North Half (1/2) North East Quarter (1/4) of thirty three (33) Township Trrenty (20) North Range Five (5) East.</p> <p>Said ditch consists of one row of 16 inch tile from the beginning to the terminus. Tile used must be of good quality, well matched and laid in a true line and at the proper grade, and must be inspected by the Engineer in charge before being covered, after being received by the engineer, the tile must be covered so the ground can be cultivated over the ditch, and to the entire satisfaction of the Engineer. A retaining wall of stone 10 feet long 4 feet high and two feet thick is to be built from field rock or rigger heads laid up in mortar made from 1 pt Portland Cement to 3 pts good sharp sand. This wall to be placed at the end of the tile at Station 32+45 feet. The tile must be imbedded in the wall at the proper grade and thoroughly mortared or slushed. The last two tile must be sewer tile.</p>							

GENERAL SPECIFICATIONS AND SUGGESTIONS.

The length of the ditch as located is 245 feet.

The fall of the established grade is 7/100 feet, from Station 0 to Station 1, is 4/100 feet, from Station 1 to Station 18, is 3/100 feet from station 21 to station 30, and is 2/100 feet from station 30 to terminus 32+45 feet.

The total fall is 11/100 feet to the whole ditch.

All timber shall be deadened for one rod on either side of the line of the ditch, and the underbrush shall be removed from the line of the ditch within the same limits.

Viewers { *J. B. Laultke*
John E. Kuckosal
John W. Knight

Subscribed and sworn to before me, this

30

day of

July

1898

Calvin Sturdevant Auditor

Hamilton County.