







Drain: ROSS ? m. Andel **Drain #:** 228
Improvement/Arm: ORR ? MYERS
Operator: J. LIVINGSTON **Date:** 6-2-04
Drain Classification: Urban/Rural **Year Installed:** 1900

GIS Drain Input Checklist

- Pull Source Documents for Scanning
- Digitize & Attribute Tile Drains
- Digitize & Attribute Storm Drains
- Digitize & Attribute SSD
- Digitize & Attribute Open Ditch
- Stamp Plans
- Sum drain lengths & Validate
- Enter Improvements into Posse
- Enter Drain Age into Posse
- Sum drain length for Watershed in Posse
- Check Database entries for errors



Gasb 34 Footages for Historical Cost Drain Length Log

Drain-Improvement: ROSS : main - ORR : MYERS

Drain Type:	Size:	Length	Length (DB Query)	Length Reconcile	If Applicable	
					Price:	Cost:
TILE	10"	1000'	1000'		3.00/lf	3000.00
	12"	2700'	2700'		4.00/lf	10,800.00

Sum: 3700' 3700' \$13,800.00

Final Report: 3700'

Comments:

No.

IN THE MATTER OF

Orr W Myers Ditch

Report of viewers appointed
May 17-1883
Ditch viewers appointed by
Heater states final report of
May 17-1883

Report of Ditch Viewers.

COMMISSIONERS' COURT.

Filed _____, 1

Auditor.

Wm. B. Bartford, Printer, Indianapolis. 500-2-25-'99.

EWB 12-362-6364

Viewers' Report of

Orr and Myers

Ditch.

To the Honorable Board of Commissioners of *Hamilton* County, Indiana:

We, the undersigned, appointed by this Court, at its *December Regular* Term, 1899, to view a drain described in the certified copy of a petition and order of Court for a *Drain*, by *Michael Orr* and others, handed us by the Auditor, would represent that according to said order we, on the day named therein, to wit: The *21st* day of *December*, 1899, in company with *J. A. Mitchell*, a civil engineer, made an accurate survey of the line of said proposed *Drain* from its source to its outlet. A plat of said *Drain* is filed herewith, including the survey by the engineer, marked "Exhibit *13*." We caused stakes to be set along said line, each one hundred feet, numbering down stream, as shown by plat. We also made a computation of the total number of cubic yards of earth to be removed from said drain, and estimated the total cost for the construction of the work at *\$623.45* Dollars.

We also apportioned and set apart to each parcel of land a share of said work in proportion to the benefits received, all of which will fully appear by a tabular statement in this report. We have also set out, by a statement below, the names of the owners of lands benefited, with a description of each tract of land, and the amount assessed against each tract. The depth of cut, the width at bottom, and width at top along said drain, is also shown in a tabular statement in this report. After a full and careful view and examination, we are of the opinion that the drain, as located by the survey, will be of public utility; and that the cost of construction will be less than the benefits to be derived therefrom; and we further believe that said drainage can best be accomplished by a tile drain from its source to its terminus as follows:- One row of 10 inch tile from stake 0 to stake 10; One row of 12 inch tile from stake 10 to stake 37 or terminus. A stone wall 10ft. long, 6ft. high and 2ft. thick at stake 37 or end of tile. To be built of field rocks laid up in Quaker made from 1 part portland cement to three parts good sharp sand; wall so constructed so as to receive the tile at the proper grade and one and one-half feet above the base of the wall: the last three tile to be sagglaged sewer tile.

The following statement shows who are benefited, the lands thereof and assessments thereon, location, length of each share, amount of assessment, amount of benefits, amount of dirt to be removed from each share, price thereof per cubic yard, and total cost of each share:

NAMES OF OWNERS.	DESCRIPTION OF LANDS.	Section.	Township.	Range.	Acres Assessed.	Ft. (1/4)ths Assessed.	Acres Benefited.	Ft. (1/4)ths Benefited.	Amount of Benefits.	Amount of Assessments.	From Station.	To Station.	Feet Long.	Cubic Yards to be Removed.	Price per Cubic Yard.	Cost of Construction of Share.
1 Michael Orr.	N.E.	NW	25 20	3	10	10	40	40	✓						375	39 28
2 M. E. Dolvin	N. SE.	SW	24 20	3	20	20	110	110	✓						9275	108.02
3 Mahala Ross Est.	" NW	NW	25 20	3	3	3	11	11	✓						9 27	10 80
4 Levi Burris	" SE	SE	23 20	3	12	12	45	45	✓						3794	44.19
5 M. L. Myers Est.	SW	SW	24 20	3	40	40	396	352	✓						296 74	345.66
"	NW	SW	24 20	3	25	25	56									
6 E. W. Chamberlain	N.E.	SE	23 20	3	40	40	34	34	✓						28 66	33.38
7 Shp. Sturdevant	N. SE	NE	23 20	3	4	4	2	2							1 68	1 96
8 Maria Richie	" NW	SE	23 20	3	1	1	1	1							85	98
9 Adams Township	Highway 8 th W. bet. 24 th & 25 th	SW	24 20	3			40	40							3375	39 28

Viewers' Report of *Orin and Myers*

Ditch.

TABULAR STATEMENT OF STATIONS, WIDTH, DEPTH, LENGTH, ETC.

STATIONS.	WIDTH AT TOP.		DEPTH OF CUT.		WIDTH AT BOTTOM.		WIDTH OF CLEARING OR TIMBER.
	Feet.	Inches.	Feet.	Tenths.	Feet.	Inches.	
<p><u>Location</u></p> <p>Beginning at a stake marked "0", 200 feet east and 16 feet south of the northwest corner of the east one-half of the northwest-quarter section 25 Township 20 North Range 3 East in Hamilton County Ind; running thence North $54\frac{1}{2}^\circ$ West, from 0 to $214\frac{1}{2}$ ft = 216.2 feet; thence North $57\frac{1}{2}^\circ$ West, from 214.62 to 26 = 43.8 feet; thence west from 26 to 37, = 11.00 feet, and terminating in an open drain known as the Mahala Road Ditch, about 20 rods north and 20 rods west of the southwest corner of the north-east quarter of the southeast quarter of section 23 Township 20 North Range 3 East</p> <p><u>Requirements.</u></p> <p>All tile to be used must be of the best quality in every respect, and must be laid in the ditch at the proper grade, in a true line with joints well matched; and must be left uncovered until inspected and accepted by the engineer in charge; after being accepted by the engineer, all earth excavated must be placed in and over the line of ditch. All material furnished, and work done must be to the entire satisfaction of the engineer.</p> <p>The timber shall be deadened for one rod on each side of the ditch; and the right of way of the line of ditch shall be cleared to the width of 8 feet</p>							

GENERAL SPECIFICATIONS AND SUGGESTIONS.

The length of the ditch as located is 3700 feet

The fall of the established grade is $\frac{16}{100}$ feet, from Station 0 to Station 37, is feet.

The total fall is $5\frac{22}{100}$ feet to the 3700 feet

The viewers would further report that in our opinion it would be impracticable to allow said ditch for construction for the reason that the work can be quicker and better done, and the cost of receiving the same will be greatly reduced therefore we would recommend that said ditch be sold by the Auditor of the County as provided by law in such cases.

Viewers { *W. C. Clark*
Jesse, 604,

Subscribed and sworn to before me, this

19th day of Jan.
Calvin Studevant

1900

Auditor

Hamilton

County.